

## 4-Fiber Parallel Indoor Cable

### Features


- Good mechanical and environmental characteristics;
- The mechanical characteristics meet the requirements of relevant standards;
- Soft, flexible, easy to splice, and with big capacity data transmission;
- Meet various requirements of market and clients.

### Application

- Used in indoor cabling
- Used as access building cable
- Used as interconnect lines of equipments, and used in optical connections in optical communication rooms and optical distribution frames;
- Used as pigtails and patch cords

### Options

- Fiber Type: G.652, G.655, G.657 single-mode fiber, A1a or A1b multi-mode fiber, or other types of fiber;
- Jacket Material: Polyvinylchloride(PVC), Low smoke zero halogen(LSZH), Thermoplastic polyurethane(TPU), or other contracted material;
- Jacket color: (including color of fiber) meets the requirements of relevant standards, or other contracted color;
- Cable Dimension: The nominal cable dimension or other contracted dimension
- Delivery Length: 1KM or 2KM or other contracted length
- Other Requirements: Other contracted special requests



### Specifications

Fiber Count	Cable Dimension (mm)	Cable Weight (kg/km)	Tensile(N)		Crush(N/100mm)		Min. bend Radius(mm)		Range of Long Temperature(°C)
			Long Term	Short Term	Long Term	Short Term	Dynamic	Static	
4-Fiber Parallel Indoor Cable									
4	3.2	8.5	80	180	200	1000	20D	10D	-20°C ~ +60°C

Note:1 D is outer diameter of the round tale

Note:2 The minimum bend radius(static) is 5D when G.657 fiber is used